EV QUICK REFERENCE GUIDE



AC Wall Box

19.2 kW


General

| Supplier | Eaton |
|-----------------------------------|---------------|
| Charger (kW) | 19.2 |
| Unit Part Number | GMEV80CMC1-WC |
| # of CCS1 Cables | 1 |
| Dual Truck Charging Capability | No |

Electrical Specs

| AC Input Voltage | 208 / 240 VAC +/- (60 Hz) |
|--|---------------------------|
| AC Input Connection | 1-Phase |
| Input Amps | 80 A |
| Recommended Upstream Circuit Breaker | 100 A |
| Cable Length (ft) | 25 |
| Commissioning | Via Eaton App |

Included in Charger Purchase



Fast and cost-effective charging for passenger vehicles. This unit combines breakout capabilities for metering control, integrated communications and access control with flexible installation options.



Green Motion

50 kW

General

| Supplier | Eaton | |
|-----------------------------------|--------------|--|
| Charger (kW) | 50 | |
| Unit Part Number | GMDC50-CCSX2 | |
| # of CCS1 Cables | 2 | |
| Dual Truck Charging Capability | Yes | |



Electrical Specs

| AC Input Voltage | 480Y / 277 VAC +/- 10% (60 Hz) |
|--|--------------------------------|
| AC Input Connection | 3-Phase |
| Input Amps | 64 A |
| DC Peak Output Power | 50 kW |
| DC Output Voltage | 200 - 1,000 VDC |
| DC Output Current | 125 A |
| Recommended Upstream Circuit Breaker | 100 A |
| Cable Length (ft) | 24.6 |
| Commissioning | Eaton Certified Installer |
| | |

Included in Charger Purchase

| Warranty (Parts) | 2 Years |
|---|----------|
| Warranty (Labor) | 90 Days |
| Charger Management Software + Cellular | 2 Years |
| Activation | Included |
| Freight | Included |

Estimated Charge Time

| Battery Capacity (kWh) | 282 | 423 | 564 | 705 |
|------------------------|-----|-----|------|------|
| Charge Time (HRS)* | 5.5 | 8.3 | 11.1 | 13.9 |

^{*} Charging times are theoretical. Thermal derating on charger and vehicle are dynamic and charging times may vary.

Green Motion

100 kW

General

| Supplier | Eaton | |
|-----------------------------------|---------------|--|
| Charger (kW) | 100 | |
| Unit Part Number | GMDC100-CCSX2 | |
| # of CCS1 Cables | 2 | |
| Dual Truck Charging Capability | Yes | |



Electrical Specs

| AC Input Voltage | 480Y / 277 VAC +/- 10% (60 Hz) |
|--|--------------------------------|
| AC Input Connection | 3-Phase |
| Input Amps | 128 A |
| DC Peak Output Power | 100 kW |
| DC Output Voltage | 200 - 1,000 VDC |
| DC Output Current | 250 A |
| Recommended Upstream Circuit Breaker | 160 A |
| Cable Length (ft) | 24.6 |
| Commissioning | Eaton Certified Installer |
| | |

Included in Charger Purchase

| Warranty (Parts) | 2 Years |
|---|----------|
| Warranty (Labor) | 90 Days |
| Charger Management Software + Cellular | 2 Years |
| Activation | Included |
| Freight | Included |

Estimated Charge Time

| Battery Capacity (kWh) | 282 | 423 | 564 | 705 |
|------------------------|-----|-----|-----|-----|
| Charge Time (HRS)* | 2.7 | 4.1 | 5.5 | 6.9 |

^{*} Charging times are theoretical. Thermal derating on charger and vehicle are dynamic and charging times may vary.

Green Motion

150 kW

General

| Supplier | Eaton |
|--------------------------------|---------------|
| Charger (kW) | 150 |
| Unit Part Number | GMDC150-CCSX2 |
| # of CCS1 Cables | 2 |
| Dual Truck Charging Capability | Yes |



Electrical Specs

| AC Input Voltage | 480Y / 277 VAC +/- 10% (60 Hz) |
|--|--------------------------------|
| AC Input Connection | 3-Phase |
| Input Amps | 192 A |
| DC Peak Output Power | 150 kW |
| DC Output Voltage | 200 - 1,000 VDC |
| DC Output Current | 300 A |
| Recommended Upstream Circuit Breaker | 250 A |
| Cable Length (ft) | 24.6 |
| Commissioning | Eaton Certified Installer |
| | |

Included in Charger Purchase

| Warranty (Parts) | 2 Years |
|---|----------|
| Warranty (Labor) | 90 Days |
| Charger Management Software + Cellular | 2 Years |
| Activation | Included |
| Freight | Included |

Estimated Charge Time

| Battery Capacity (kWh) | 282 | 423 | 564 | 705 |
|------------------------|-----|-----|-----|-----|
| Charge Time (HRS)* | 1.7 | 2.7 | 3.6 | 4.5 |

^{*} Charging times are theoretical. Thermal derating on charger and vehicle are dynamic and charging times may vary.

PacMobile

60 kW

General

| Supplier | Heliox |
|--------------------------------|-------------|
| Charger (kW) | 60 |
| Unit Part Number | MB060-1-001 |
| # of CCS1 Cables | 1 |
| Dual Truck Charging Capability | No |



Electrical Specs

| AC Input Voltage | 480Y / 277 VAC +/- 10% (60 Hz) | | | |
|--|--------------------------------|--|--|--|
| AC Input Connection | 3-Phase | | | |
| Input AC Current & Full Load | 90 A, 65 kVA | | | |
| DC Peak Output Power | 60 kW | | | |
| DC Output Voltage | 200 - 1,000 VDC | | | |
| DC Output Current | 150 A | | | |
| Recommended Upstream Circuit Breaker | 100 A | | | |
| Cable Length (ft) | 16 on both sides | | | |
| Commissioning | Site Electrician | | | |
| | | | | |

Included in Charger Purchase

| Cellular Connection | Included |
|---------------------|----------|
| Activation | Included |

Estimated Charge Time

| Battery Capacity (kWh) | 282 | 423 | 564 | 705 |
|------------------------|-----|-----|-----|------|
| Charge Time (HRS)* | 4.5 | 6.9 | 9.2 | 11.6 |

^{*} Charging times are theoretical. Thermal derating on charger and vehicle are dynamic and charging times may vary.

PacCharge 60 kW

General

| Supplier | Heliox |
|--------------------------------|-------------|
| Charger (kW) | 60 |
| Unit Part Number | MB060-1-002 |
| # of CCS1 Cables | 1 |
| Dual Truck Charging Capability | No |



Electrical Specs

| 480Y / 277 VAC +/- 10% (60 Hz) | | |
|--------------------------------|--|--|
| 3-Phase | | |
| 90 A, 65 kVA | | |
| 60 kW | | |
| 200 - 1,000 VDC | | |
| 150 A | | |
| 100 A | | |
| 16' | | |
| Site Electrician | | |
| | | |

Included in Charger Purchase

| Cellular Connection | Included |
|---------------------|----------|
| Activation | Included |

Estimated Charge Time

| Battery Capacity (kWh) | 282 | 423 | 564 | 705 |
|------------------------|-----|-----|-----|------|
| Charge Time (HRS)* | 4.5 | 6.9 | 9.2 | 11.6 |

^{*} Charging times are theoretical. Thermal derating on charger and vehicle are dynamic and charging times may vary.

Flex 180 kW

General

| Supplier | Heliox | | |
|--|------------------|--|--|
| Charger (kW) | 180 (60 kW each) | | |
| Unit Part Numbers FL-180-001 & HE2120139 | | | |
| # of CCS1 Cables | Up to 3 | | |



Electrical Specs

| 480Y / 277 VAC +/- 10% (60 Hz) | | |
|--------------------------------|--|--|
| 3-Phase | | |
| 246 A / 100 VA | | |
| 180 kW | | |
| 150 - 1,000 VDC | | |
| 250 A Single 83 A Triple | | |
| 300 A | | |
| 23 | | |
| Heliox Technician | | |
| | | |

Included in Charger Purchase

| Cellular Connection | Included |
|---------------------|----------|
| Warranty (Years) | 2 |
| Charger Site Access | Included |

Estimated Charge Time

| Battery Capacity (kWh) | 282 | 423 | 564 | 705 |
|------------------------|-----|-----|-----|-----|
| Charge Time (HRS)* | 1.5 | 2.4 | 3.2 | 4.1 |

^{*} Charging times are theoretical. Thermal derating on charger and vehicle are dynamic and charging times may vary.

Add-ons & Services

Add-Ons

| BABA / BAA Chargers | |
|-------------------------------|--|
| Cellular Connectivity | |
| Flexible Installation Options | |
| Light Duty Vehicle Chargers | |
| Locks and Keys | |
| Pedestals | |
| RFID Cards | |
| Vandalism Discounts | |
| Various Cable Lengths | |
| | |

Services

| Extended Service Level Agreement | |
|----------------------------------|--|
| Extended Software Coverage | |
| Extended Warranty | |
| Payment Portal | |
| Preventative Maintenance | |
| Reporting Tools | |
| Service Level Agreement Coverage | |
| Software Providers | |
| Technical Support | |
| Warranty Coverage | |

For more information on various options and accessories please reach out to your local dealer or contact EVCharging@PACCAR.com for assistance.



For more information please reach out to your local dealer or contact EVCharging@PACCAR.com for assistance.